

TeleOperationStation: XR-Exploration of User Interfaces for Remote Automated Vehicle Operation

Michael Gafert

michael.gafert@ait.ac.at

AIT Austrian Institute of Technology
Vienna, Austria

Peter Fröhlich

peter.fröhlich@ait.ac.at

AIT Austrian Institute of Technology
Vienna, Austria

Alexander G. Mirnig

alexander.mirnig@ait.ac.at

AIT Austrian Institute of Technology & University of
Salzburg
Austria

Manfred Tscheligi

manfred.tscheligi@ait.ac.at

AIT Austrian Institute of Technology & University of
Salzburg
Austria



Figure 1: The VR operation station (left) and the vehicle equipped with four 120° cameras and proximity sensors in the physical model environment (right).

ABSTRACT

With increased automation levels of vehicle technology, human involvement is expected to be transformed from a driver towards an operator role. This transition will entail remote monitoring and possibilities for intervention of driverless vehicle fleets. Thus far, there are insufficient tools available for user interface development and experimentation, which renders it difficult to quickly devise, prototype, and test solutions to support operators in their specific work contexts. We present the TeleOperationStation, an extended-reality experience prototyping environment, which coherently simulates automated fleet operation work flows, covering non-driving tasks, monitoring, takeover requests, and full remote vehicle operation. During this interactive demonstration, on-site and online conference participants will be enabled to experience and co-create user

interfaces for remote automated vehicle operation, using AR from a first-person viewpoint, and controlling a physical miniature vehicle.

CCS CONCEPTS

• **Human-centered computing!** *HCI design and evaluation methods; Systems and tools for interaction design.*

KEYWORDS

Human-Computer Interaction (HCI), remote operation, teleoperation, automated vehicles

ACM Reference Format:

Michael Gafert, Alexander G. Mirnig, Peter Fröhlich, and Manfred Tscheligi. 2022. TeleOperationStation: XR-Exploration of User Interfaces for Remote Automated Vehicle Operation. In *CHI Conference on Human Factors in Computing Systems Extended Abstracts (CHI '22 Extended Abstracts)*, April 29-May 5, 2022, New Orleans, LA, USA. ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/3491101.3519882>

1 INTRODUCTION AND MOTIVATION

The introduction of automated vehicles is expected to transform the management of vehicle fleets in individual and public transportation [8], as well as freight transport and intralogistics [2, 3]. With increased automation levels of vehicle technology, the role of the

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

CHI '22 Extended Abstracts, April 29-May 5, 2022, New Orleans, LA, USA

© 2022 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-9156-6/22/04.

<https://doi.org/10.1145/3491101.3519882>

driver will shift towards an operator and passenger. Moreover, monitoring and control interventions will increasingly be performed from remote locations, whereby operators may have to manage an increasing number of vehicles at the same time. As a consequence, human factors research has started to define requirements for the support of human remote operation of driverless automated vehicles, [1, 5–7]. The need for interactive prototypes for testing novel UI features for remote operation has been recognized, but experimental environments are restricted to highly specialized scenarios and functionalities, such as predictive displays for specific cars [4] or for public transportation scenarios [8].

Consequently, it has so far been difficult to iteratively test new ideas scenarios that are representative for the work context of a remote operator. Figure 2 illustrates a typical workflow which often involves non-driving related tasks, in which the vehicles are driving autonomously. In case of an event in which the automated vehicle needs an operator to refocus her/his attention, a takeover request has to be issued by the system that suits the respective work situation. The system then has to provide the operator with an overall briefing of the situation (i.e. about the overall position of the system, the problem that occurred, and potentially recommended further actions).

When the operator has then achieved situational awareness and decides to intervene by a teleoperation, he/she needs to be prepared for teleoperation. Once situation awareness has been received to the required operational level (e.g. having oriented from a first-person perspective, knowing where to drive, recognize the surrounding traffic, other road users and obstacles), the operator performs the remote driving activity, navigates and, if necessary, communicates with other process participants. After the teleoperation phase, the human operator then should be prepared for the non-driving related task and the handover should be realized.

To help evaluate different interaction methods and HMI aspects throughout this cycle we present "TeleoperationStation" - a pervasive experience prototyping environment for developing and testing automated vehicle fleet operations in extended reality. Its core is a miniature vehicle which is controlled remotely by a human operator. Operation via VR with visuals only coming from vehicle-mounted cameras provides a low-cost setup with a high degree of realism and immersion. Deployment of the vehicle in a miniature environment instead of a fully simulated one provides a degree of physicality and further enhances its ecological validity.

2 DESIGN GOALS

In order to achieve its intended contribution, TeleOperationStation follows the following design goals:

Coherent experience simulation of automated fleet operation workflows: Through VR simulation, the flow from a non-driving task, as depicted in Figure 2, can be experienced. This makes it possible to design for control transitions and enables the imagination of cognitive load and situation awareness requirements of teleoperation tasks.

Physical setup of teleoperated vehicles: We developed this physical setup, in contrast to driving simulations [9], to prevent the operator from disconnecting with reality and having

video game like experiences. Because of the miniature aspect, it still allows for user errors, like crashing into the environment, which are not feasible with real vehicles.

Teleoperation assistance and automation features: Built-in sensors on the vehicle, including cameras, micro-lidars and others enable the investigation of assistance features for remote operation.

Open configuration and adaptation: The situation this setup allows for rapid use case development as the environment itself is built with paper cutouts and can simply be re-situated according to another driving task. Therefore, software development is needed when evaluating different environments. Code and templates for materials are provided open source.

3 SYSTEM AND ENVIRONMENT DESCRIPTION

In the following, an overview of the XR architecture of TeleOperationStation is provided, and physical vehicle and environment are described.

3.1 XR architecture

The remote automated vehicle management operator is equipped with different displays for remote management of fleets. In case a vehicle has to be directly teleoperated, VR glasses are used, in combination with the steering wheel (hardware and/or virtual representation via Varjo XR-3¹ or Oculus Quest 2² hand tracking). The VR environment is realized by Unity³. It consists of the video feeds, a floating user interface pane and the steering wheel. On a primary display, the visual information directly related to the visual scene is provided, including 360° camera streams and sensor-based proximity cues. This information is streamed from the four cameras and sensors mounted on the vehicle to Unity. Secondary displays contain additional elements, such as non-spatially oriented UI elements displayed on the floating 2D pane.

3.2 UI experimentation

User interface features can be made available on the primary or on a secondary display, based on the requirements from Graf and Hussmann [5]. Apart from information about the status of relevant vehicle parts (tires, light, weight), these include means for spatial orientation, such as a 360° remote view, and navigation. They can also include a marker indicating the vehicle heading (similarly to [4]), the display of the predicted driving lane and further landmarks. Furthermore, information on the respective driving task can be provided (such as time constraints, tasks to complete, task priority, as well as the projected need to shed tasks). Also, information on the quality of the communication line (about the available bandwidth and signal strength, the mobile carrier) and sensing reliability (camera status) can be given.

3.3 The Vehicle

The vehicle consists of custom hard- and software. The chassis was 3D printed in a FDM (Fused Depositing Modelling) printer and

¹<https://varjo.com/products/xr-3>

²<https://www.oculus.com/quest-2/>

³<https://www.unity.com>

5 CONCLUSIONS AND OUTLOOK

TeleOperationStation is an interactivity demo to showcase challenges and potential solutions regarding design and experience of remote operation of an automated vehicle fleet. The virtual cockpit allows for effective prototyping of different control interfaces and can be extended with, e.g., mission status or task information for integration into a fleet operation cycle. The physical driving environment reduces the need for virtual environment modelling and provides an additional degree of tangibility. Physics also do not need to be modeled, since the vehicle and its environment are not virtual.

Through the immersion enabled by the extended reality setup, on-site and virtual visitors can gain novel insights and exchange. The system is ready to be used in its current state (and is actively being used within the AWARD project) but we also work on improving and extending it further, based on results and lessons learned from user studies. Thanks to the modular setup, extensions and modifications can be done with reduced effort and others who want to use or adapt it can choose to use all or only parts of it.

Conceptualized as a research environment, TeleOperationStation is intended to be openly used by anyone interested. All required components are available off the shelf, and instructions on how to assemble them are provided in an open repository. With public demonstrations such as the one planned for this conference, we expect a more successful uptake of safe and operator-friendly remote management technologies for automated transport.

ACKNOWLEDGMENTS



This work is part of the project AWARD, which has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 101006817. The content of this paper reflects only the author's view. Neither the European Commission nor CINEA is responsible for any use that may be made of the information it contains.

REFERENCES

- [1] Mutzenich Clare, Durant Szonya, Shaun Helman, and Polly Dalton. 2021. Updating our understanding of situation awareness in relation to remote operators of autonomous vehicles. *Cognitive Research* 6, 1 (2021).
- [2] Peter Fröhlich, Michael Gafert, Lisa Diamond, Martin Reinthaler, Matthias Neubauer, Florian Hammer, and Sami Koskinen. 2021. Towards a Comprehensive Understanding of Stakeholder Requirements for Automated Road Transport Logistics. In *Proceedings of the CHI2021 Workshop "Automation Experience at the Workplace"*. CEUR Proceedings.
- [3] Michael Gafert, Peter Fröhlich, Ulrike Ritzinger, and Matthias Baldauf. 2021. Challenges for Future Automated Logistics Fleet Interactions. In *Proceedings of the CHI 2021 Workshop "Automation Experience at the Workplace"*. CEUR Proceedings.
- [4] Jean-Michael Georg and Frank Diermeyer. 2019. An Adaptable and Immersive Real Time Interface for Resolving System Limitations of Automated Vehicles with Teleoperation. In *2019 IEEE International Conference on Systems, Man and Cybernetics (SMC)*. 2659–2664. <https://doi.org/10.1109/SMC.2019.8914306> ISSN: 2577-1655.
- [5] Gaetano Graf and Heinrich Hussmann. [n. d.]. User requirements for remote teleoperation-based interfaces. In *Adjunct Proceedings - 12th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications, AutomotiveUI 2020* (2020). Association for Computing Machinery, Inc, 85–88. <https://doi.org/10.1145/3409251.3411730>
- [6] Gaetano Graf, Henri Palleis, and Heinrich Hussmann. [n. d.]. A Design Space for Advanced Visual Interfaces for Teleoperated Autonomous Vehicles. In *ACM International Conference Proceeding Series* (2020). Association for Computing Machinery. <https://doi.org/10.1145/3399715.3399942>
- [7] Carmen Kettwich and Annika Dreßler. 2020. Requirements of Future Control Centers in Public Transport. In *Adjunct Proceedings - 12th International ACM Conference on Automotive User Interfaces and Interactive Vehicular Applications, AutomotiveUI 2020*. Association for Computing Machinery, Inc, 69–73. <https://doi.org/10.1145/3409251.3411726>
- [8] Carmen Kettwich and Andreas Gottfried Schrank. 2021. Teleoperation of Highly Automated Vehicles in Public Transport: State of the Art and Requirements for Future Remote-Operation Workstations. (2021).
- [9] Dohyeon Yeo, Gwangbin Kim, and Seungjun Kim. 2020. Toward Immersive Self-Driving Simulations: Reports from a User Study across Six Platforms. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems* (Honolulu, HI, USA) (CHI '20). Association for Computing Machinery, New York, NY, USA, 1–12. <https://doi.org/10.1145/3313831.3376787>